

Mining

T-707 AA

**MINE SLURRY SUCTION &
DELIVERY 10 BAR (150 PSI) -
MUFF COUPLINGS**


TUBE	BLACK CONDUCTIVE NR - ABRASION RESISTANT APPROX. 50 mm3 (ISO 4649/A)
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRES
COVER	BLACK CONDUCTIVE SBR/NR BLEND - ABRASION AND OZONE RESISTANT
APPLICATION	BULK MATERIAL AND ABRASIVE SLURRIES SUCTION AND DELIVERY. LONG LASTING SERVICE IN HEAVY DUTY MINING APPLICATIONS. DESIGNED FOR MUFF COUPLINGS USE.
TEMPERATURE	-30°C +80°C (-22°F +176°F)
BRAND TEXT	ALFAGOMMA -ITALY- T-707 10 BAR (150 PSI) BULK MATERIAL / MINE SLURRY S&D (omega)
BRAND TYPE	WHITE LETTERS
NOTE	
APPROVALS	
SAFETY FACTOR	3:1

Code	ID mm	ID Inch	OD mm	Wall mm	Weight g/m	WP bar	WP PSI	Vac. %	BR mm	Available Length m	Stock Length m
707AA051697UB0	51	2	69	9	2220	10	150	90	304	20/61	
707AA076987UB0	76	3	98	11	4120	10	150	90	304	20/30,5	
707AA102247UB0	102	4	124	11	5400	10	150	90	408	20/30,5	
707AA152787UB0	152	6	178	13	9360	10	150	80	760	20/30,5	
707AA203377UB0	203	8	237	17	17320	10	150	70	1015	10/12,2	
707AA254927UB0	254	10	292	19	23720	10	150	70	1270	10/12,2	