



## Air and Multi-Purpose Hose

# Diesel Exhaust Fluid

(Specification 4217IS)

Nom. I.D.	⊖	Nom. O.D.	⊖	Max. W.P.	⌚	Suction	⊖	Min. Bend Radius	⌚	Wt. Per Ft.	⚖	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
3/4	19.1	1.13	28.5	350	2.40	15.0	381	4.0	101.6	.27	.12	Reel	X	4217-0310	\$6.76
1	25.4	1.36	34.5	350	2.40	10.0	254	6.0	152.4	.41	.19	Reel	X	4217-0311	9.82

- RECOMMENDED FOR:** Transfer of urea solutions such as ADBLUE.
- TEMPERATURE:** -40°F to +212°F (-40°C to +100°C) continuous service.
- CONSTRUCTION:** **Tube:** Type P (EPDM). Black - Peroxide Cured - No Zinc.  
**Reinforcement:** Synthetic, high tensile textile cord.  
**Cover:** Type P (EPDM). Black. Wrapped appearance.  
**Design Factor:** 4:1
- COUPLINGS:** 75 Gates GLX® or stainless steel. Reference the Hose Coupling Section.
- PACKAGING:** 3/4": Packaged in 450' to 650' reels. Maximum 4 pieces. One piece allowed under 100'. Minimum length 15'.  
 1": Packaged in 300' to 500' reels. Maximum 5 pieces. Minimum length 15'.
- BRANDING:** Continuous ink brand. Example: "GATES® DIESEL EXHAUST FLUID DISPENSING 3/4" (19.1mm) 350 PSI(2.4 MPa) WP Made in USA"
- SPECIAL ORDER REQUIREMENTS:** Special production runs require minimum order quantities of 5,000 feet.
- REMNANT LENGTHS:** None.
- STANDARDS:** **Tube:** Zinc and Calcium Carbonate Free.

ACID-CHEMICAL
AIR AND MULTI-PURPOSE
FOOD AND BEVERAGE
MARINE
MATERIAL HANDLING
MINING
OILFIELD
PETROLEUM TRANSFER
PRESSURE WASHER
STEAM
WATER
CLAMPS
COUPLINGS AND FERRULES
HOSE FINDER
CHEMICAL RESISTANCE TABLE

