

Vapour Hose

Applicable Standards:
BS EN 13765: Type 1

Temperature Range: -30°C to +80°C
Pressure range: Norm. 7 bar – but higher can be accommodated.

Danoil VR GG, SG, SS. is a composite hose, purpose built for vapour return of hydrocarbon products in marine, road and rail tanker operations. With Dantec Sure-lec guaranteed electrical continuity.

Danchem VR is of similar construction to Danoil VR but is suitable for more aggressive chemical applications



Dantec Vapour hoses are robust, but light weight, extremely flexible with the same specially high strength cover as used on all Dantec composite hose.

Sizes 1" to 10". Standard Colour: Orange or Yellow.

Bore Diameter		Max. Working Pressure		Bend Radius		Weight	
INS	MM	BARS	PSI	INS	MM	KG/M	LB/FT
3	75	7	100	4.0	100	2.4	1.6
4	100	7	100	5.5	140	3.4	2.3
6	150	7	100	7.0	180	8.3	5.6
8	200	7	100	8.0	205	12.5	8.4
10	250	7	100	11.0	280	16.0	10.7



Tel: +44 (0)151 678 2222
Fax: +44 (0)151 606 0188
Email: sales@dantec.ltd.uk

DAN www.dantec.ltd.uk
TEC World Leader in Composite Hose Technology