


Viton-lined Smooth Bore Petrochemical Suction & Discharge Hose

Type 383V



Application	Lightweight, flexible hoses offering easy handling. Generally used at dockside and jetty locations where the working conditions do not call for high crush resistance or tensile strength.		
Specification	Generally to BS EN 1765:2004 S15	Working / Burst Pressures	15 / 60 Bar

Hose Component	Description
Lining	Viton rubber compound for petroleum products with an aromatic content up to 100% and many industrial chemicals.
Main reinforcement	Multiple plies of high tenacity rayon cord designed for a combination of high strength and resistance to fatigue. Each layer is fully encapsulated in rubber to prevent abrasion with adjacent layers.
Embed wire	Helical steel wire to resist collapse and crush loads
Holding ply	Textile reinforcement to increase adhesion between hose body and cover
Cover	Weathering and abrasion resistant rubber compound
Fittings	Built-in steel nipples with flanges to suit customer requirements.

Hose Characteristics									
	2in.	2.5in.	3in.	4in.	5in.	6in.	8in.	10in.	12in.
Internal Diameter (mm)	50.8	63.5	76.2	101.6	127	152.4	203.2	254	304.8
Outside Diameter (mm) (nominal)	85	97	111	136	163	195	252	303	359
Hose Body Weight (kg/m)	5.4	6.4	7.9	10	13	18.9	28.1	36.4	46.9
Hose End Weight (kg/hose)	11	14	18	29	38	46	67	96	122
Min. Bend Radius (m)	0.3	0.38	0.46	0.6	0.76	0.9	1.2	1.5	1.8
Safe Working Tensile Load (tonnes)	1.1	1	1.6	1.3	2.4	3.4	6.7	7.4	6.3
Operating Temperature (all sizes)	-20°C to +100°C								
Electrical Continuity	Electrically continuous or discontinuous as required.								
<i>For alternative sizes, lining materials or pressure / temperature ratings please contact us.</i>									



Dunlop Oil & Marine Ltd
 Moody Lane, Pyewipe
 Grimsby, DN31 2SY
 England

T: +44 (0) 1472 359281
 F: +44 (0) 1472 362948
 E: dunlop.sales@dunlop.co.uk
www.dunlop-oil-marine.co.uk



ContiTech Division
 of Continental AG