



Hot Water (10 bar W.P. 30 bar B.P.) & Steam Hose (6 bar W.P. 60 bar B.P.)



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg	lbs	m	ft
1401700	13	1/2	23	0.91	10	150	30	450	0.32	0.22	120	400
1402897	16	5/8	26	1.02	10	150	30	450	0.38	0.25	120	400
1401963	19	3/4	29	1.14	10	150	30	450	0.43	0.29	120	400
1400886	25	1	35	1.38	10	150	30	450	0.54	0.36	120	400
1415743	32	1-1/4	46.5	1.83	10	150	30	450	1.07	0.72	120	400
1425510	38	1-1/2	54	2.13	10	150	30	450	1.35	0.91	120	400
1401971	51	2	69.5	2.74	10	150	30	450	2.09	1.41	120	400

Application

Softwall hose for delivery of hot water and steam used to wash down in dairies, slaughterhouses and in the food industry in general.

Temperature

-30°C +95°C hot water

-30°C +165°C steam

Construction

Tube

White/IIR with IIR tube in accordance to FDA title 21, item 177.2600 and BfR/XXI Cat.2

Food grade

Reinforcement

High strength synthetic cord.

Cover

White, smooth (wrapped finish), synthetic rubber, fatty food and weathering resistant

Branding

Continuous red stripe "IVG HOT (family logo)..."

We will no longer stock

- × Michigan
- × Manitoba White
- × White Food/ Steam T350LL

Size	Product Code
13 mm	05 43013
19 mm	05 43019
25 mm	05 43025

