

T-706 AA
**BULK MATERIAL SUCTION
& DELIVERY 10 BAR (150
PSI) - MUFF COUPLINGS**


TUBE	BLACK CONDUCTIVE NR - ABRASION RESISTANT APPROX. 50 mm3 (ISO 4649/A)
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRES
COVER	BLACK CONDUCTIVE SBR/NR BLEND - ABRASION AND OZONE RESISTANT
APPLICATION	BULK MATERIAL AND ABRASIVE SLURRIES SUCTION AND DELIVERY. LONG LASTING SERVICE IN HEAVY DUTY APPLICATIONS. DESIGNED FOR MUFF COUPLING USE.
TEMPERATURE	-30°C +80°C (-22°F +176°F)
BRAND TEXT	ALFAGOMMA -ITALY- T-706 10 BAR (150 PSI) BULK MATERIAL HANDLING - S&D (omega)
BRAND TYPE	WHITE LETTERS
NOTE	
APPROVALS	
SAFETY FACTOR	3:1

Code	ID mm	ID Inch	OD mm	Wall mm	Weight g/m	WP bar	WP PSI	Vac. %	BR mm	Available Length m	Stock Length m
706AA076027UD0	76	3	102	13	4850	10	150	90	304	20/30,5	
706AA102287UD0	102	4	128	13	6310	10	150	90	408	20/30,5	
706AA127597UD0	127	5	159	16	9440	10	150	80	635	20/30,5	
706AA152847UD0	152	6	184	16	11420	10	150	80	760	20/30,5	
706AA203357UD0	203	8	235	16	15480	10	150	70	1015	10/12,2	
706AA254867UD0	254	10	286	16	21600	10	150	60	1270	10/12,2	
706AA300447UD0	300	11 13/16	344	22	34490	10	150	60	1500	10/12,2	