

## Air & Multi-Purpose Hose

# 319MB Gold Master (Specification 3619G/3619GL)



Nom. I.D.		Nom. O.D.		Maxi. W.P.		Suction		Min. Bend Radius		Kg. Per	Standard Pack	Part No.
(In.)	(mm)	(In.)	(mm)	(psi)	(Mpa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(m.)	(m.)	
1/4	6.4	0.63	15.9	1000	6.90	30.0	762	3.0	76	0.36	76	3619-0200
3/8	9.5	0.77	19.6	1000	6.90	30.0	762	3.0	76	0.51	76	3619-0210
1/2	12.7	0.92	23.4	1000	6.90	30.0	762	5.0	127	0.67	76	3619-0220
3/4	19.1	1.21	30.7	1000	6.90	25.0	635	7.9	209	0.97	76	3619-0230
1	25.4	1.46	37.1	1000	6.90	25.0	635	11.0	279	1.24	15	3619-0239
1 1/4	31.8	1.69	42.9	1000	6.90	20.0	508	15.9	406	1.46	15	3619-0600
1 1/2	38.1	1.94	49.3	1000	6.90	15.0	381	17.9	457	1.58	15	3619-0620
2	50.8	2.46	62.5	1000	6.90	10.0	254	25.0	635	2.24	15	3619-0630

### Recommended for:

319MB is ideal for High-pressure water and oil applications requiring good kink resistance and excellent flexibility. Also washdown service to 212°F (100°C) in packing plants where a non-marking cover is required. Cover is resistant to weather, oil, animal fat, abrasion and heat encountered in packing plant cleaning applications.

NOTE: Air service working pressure is 300psi for all sizes.

**Temperature:** -40°C to +100°C air service.

### Construction:

**Tube:** Type A (Neoprene). Black.

**Reinforcement:** Braided, high tensile steel wire.

**Cover:** Type M (Hypalon). Gold (non-marking).

All sizes are perforated.


**Couplings:** Gates MegaCrimp.

### Packaging:

**1" through 2":** 15m length coiled in a carton.

**1/4" through 3/4":** Packaged in 60m to 91m reels. Maximum of 3 pieces. Minimum length 7m. One length under 30m.

**Branding:** Continuous transfer label.

Example:  319MB Gold Master® Multi-Purpose 3/8" (9.5mm)

1000 PSI (6.90MPa) WP Made In U.S.A.

### Standards:

**Tube:** RMA (Class B) Medium oil resistance.

**Cover:** RMA (Class B) Medium oil resistance.