



OTHER APPLICATIONS  
**SATURNO**



**SATURNO**

**Colour:** green with cream helix.

**Temperature range:** - 10°C + 60°C / + 14°F + 140°F.

**Features:** Pvc hose reinforced with an anti-shock rigid Pvc spiral. Inside surface smooth, light corrugation outside. Strong and flexible, resistant to crushing, abrasion, atmospheric agents and most chemicals.

**Applications:** excellent for suction in general, particularly suitable to be used on slurry machines.

**Can be manufactured antistatic upon request**

Technical Data

Part Number	Inside Ø	Min. Wall Thickness	Max. Wall Thickness	Weight	Working Pressure	Bursting Pressure	Vacuum	Bending	Roll Length	Volume
	mm	mm	mm	g/m	bar	bar	m H2O	mm	m	m <sup>3</sup>
SL 01 019.0 000.	19,1	2,2	2,9	210	5,0	15	6	110	50	0,064
SL 01 020.0 000.	20	2,2	2,9	220	5,0	15	6	110	50	0,066
SL 01 025.0 000.	25	2,3	3,0	280	5,0	15	6	140	50	0,099
SL 01 030.0 000.	30	2,3	3,1	340	5,0	15	6	170	50	0,116
SL 01 032.0 000.	31,8	2,4	3,2	370	5,0	15	6	180	50	0,128
SL 01 035.0 000.	35	2,5	3,3	420	5,0	15	6	195	50	0,154
SL 01 038.0 000.	38,1	2,6	3,4	470	5,0	15	6	210	50	0,182
SL 01 040.0 000.	40	2,6	3,5	510	5,0	15	6	220	50	0,199
SL 01 045.0 000.	45	2,7	3,6	590	5,0	15	6	250	50	0,231
SL 01 050.0 000.	50	3,0	3,8	710	5,0	15	6	270	50	0,289
SL 01 052.0 000.	50,8	3,0	3,8	720	5,0	15	6	270	50	0,293
SL 01 060.0 000.	60	3,0	4,0	870	5,0	15	6	330	50	0,446
SL 01 063.0 000.	63,5	3,0	4,0	920	5,0	15	6	350	50	0,483
SL 01 070.0 000.	70	3,2	4,3	1060	4,0	12	6	450	50	0,531
SL 01 076.0 000.	76,2	3,3	4,4	1180	4,0	12	6	500	50	0,647
SL 01 080.0 000.	80	3,6	4,8	1350	4,0	12	6	550	50	0,702
SL 01 100.0 000.	100	4,6	6,1	2220	3,0	9	6	710	30	0,717
SL 01 102.0 000.	102	4,6	6,1	2260	3,0	9	6	710	30	0,730

Please contact us for other sizes