

VULCANO TPR R

Colour: Black

Temperature Range: -40°C - +125°C

Applications: Hot air up to 125°C (250°F), air conditioning, exhaust gas and chemicals vapours, as a duct in the automotive industry.

Features: Santoprene® coated polyester fabric duct, reinforced by a metal wire. More robust than vulcano tpr A, is resistant to high temperature and to most chemicals as well as to abrasion and tearing.



Inside Ø mm	Min. Wall Thickness mm	Weight g/m	Vacuum m H2O	Bending radius mm	Roll Length m	Volume m ³
40	0,45	160	2,0	40	20	0,079
51	0,45	200	2,0	60	20	0,107
60	0,45	235	1,7	70	20	0,137
63	0,45	245	1,7	70	20	0,150
70	0,45	315	1,7	80	20	0,182
76	0,45	340	1,7	80	20	0,233
80	0,45	355	1,6	90	20	0,254
90	0,45	400	1,6	100	20	0,295
102	0,45	450	1,3	110	15	0,286
110	0,45	560	1,2	120	15	0,319
120	0,45	610	1,0	130	15	0,370
127	0,45	645	1,0	140	15	0,404
130	0,45	660	0,8	140	15	0,426
140	0,45	690	0,8	150	15	0,504
152	0,45	750	0,8	170	15	0,544
160	0,45	780	0,7	180	15	0,662
180	0,45	880	0,5	200	15	0,851
203	0,45	990	0,4	220	15	1,140
228	0,45	1110	0,4	250	10	0,929
254	0,45	1390	0,4	280	10	1,185
279	0,45	1530	0,4	310	10	1,404
305	0,45	1670	0,3	340	10	1,610
356	0,45	1950	0,3	390	10	1,966
406	0,45	2220	0,3	450	10	2,401